



动力线插座引出线定义 Power cable connector specification	引出线标识 Pin No.	动力线插头 Power cable connector
U	B	
V	I	
W	F	
FG1	C	
FG2	D	
B1	G	
B2	H	

注：若电机不带制动器，则动力线插座无B1、B2信号
Note:If motor without holding brakes,there is no B1 and B2 signal on the Power cable connector

引出线标识 Pin No.	编码器插座引出线定义 Encoder connector specification	编码器插头 Encoder connector
1	SD+	
2	SD-	
3	BAT+	
4	BAT-	
5	/	
6	/	
7	GND	
8	VCC	
9	/	
10	FG	

技术说明(Note):

1.带油封电机，油封材质为氟橡胶，正常工作使用要求：压力≤0.04MPa
For mortor with oil seal,oil seal material is fluorine rubber,normal operation requirements:pressure≤0.04MPa

电机型号 Motor model	编码器类型 Encoder model	电机重量 (Kg) Weight (Kg)	电机本体尺寸 (mm) External dimensions (mm)		
EM3G-18 A/D LA214/224	L: 23位绝对值编码器 L: 23 bit absolute encoder	8.32	LL	KB1	KB2
EM3G-13 A/D LA214/224		7	161	124.5	146
EM3G-09 A/D LA214/224		5.6	146	109.5	131
			131	94.5	116